

UIN-D3332BHH2-E4

32CH/4HDD/H.265/5MN no real-time DVR



1. Features

- **TVI / AHD / DVR / NVR / CVI five-in-one function, multi-mode input, support HD analog video encoding, support HD analog + HD network video input, support pure HD network video input.**
- **Easily implement network penetration through cloud services and remote monitoring in one step.**
- **Supports various mobile phone monitoring (iPhone Android).**
- **Support multiple web browsers (IE / Chrome / Firefox / Safari).**
- **Support VGA,TV,HDMI output at the same time.**
- **Powerful network services (supporting DHCP, PPPOE, FTP, DNS, DDNS, NTP, UPNP, Email, etc.), complete supporting facilities (WEB, client, SDK), easily achieve interconnection and interoperability.**
- **Supports more than 20 languages and breaks the limits of national borders.**
- **Freely change the startup interface and choose the interface style.**
- **Support basic intelligence and tripwire perimeter functions.**
- **Support coaxial audio.**
- **Support Dana Cloud Taoshi Cloud cloud platform customization.**

2. Technical parameters

	Model	UIN-D3332BHH2-E4
System	Master chip	H13531A
	AD chip	TP2830
	RAM	16G
	Compression format	H.265X

	operating system	Embedded Linux operating system
Video	Input	32
	Preview	32 * 5MN/12fps
	Coding	32 * 5MN/6fps
	Decoding	16 * 5MN/6fps
	VGA output	1080P
	BNC output	support
	HDMI output	1080P
Audio	Audio Input	16
	Audio output	1
	Coaxial audio	16
	Two-way intercom	support
Playback	Number of real-time recording channels	32-way non-real-time
	Video mode	Timing, manual, motion detection, external alarm
	The number of simultaneous playback	16
	Search mode	Point-in-time search, calendar search, event search, channel search
Backup	USB mobile hard disk, U disk	support
	USB DVD burner	support
	Format	H.26X、AVI
Remote access	Browser	Supports multiple web browsers
	Client	Support VMS
	APP	Support for iPhone, Android
Storage	HDD number	4
	E-SATA	not support
Network	Network port	10 / 100/1000 Mbps Ethernet (RJ-45)
	Network protocol	TCP/IP, DHCP, DDNS, NTP, SMTP
Other	remote control	support
	power supply	DC12V /2A
	Work Temperature	-10° C ~60° C
	Working humidity	10% ~ 90% Humidity