



# IPB-354S

4 MP Fixed Turret Network Camera



## ■ Features

- H.265/H.264 4MP IP/Network IR Small Turret Dome Camera
- Up to 4 megapixel high resolution
- Max. 2560 x 1440(4MP)@30fps(50HZ/60HZ)
- Support RTSP&Onvif(17.2 with profile S) Compatible with many third-party NVRs and CMS
- Support multiply Web Browsers: IE/Firefox/Chrome/Safari etc.
- P2P Cloud service
- Free PC Client Software and Smartphone APP(P2P)
- Support Alarm Snapshot to Email and FTP
- Day/Night, AWB/MWB,BLC, 3D-DNR,Shutter, IR-CUT D-WDR,Mirror, Image Flip etc. Functions
- Audio in/out Optional (RCA Cable Interface)
- 12V DC (PoE Optional)
- 3.6mm fixed lens
- IR range: up to 15m
- Water-proof: IP66





# IPB-354S

4 MP Fixed Turret Network Camera

## ■ Specification

### Camera

Image Sensor:	1/2.7" CMOS sensor
Signal System:	PAL/NTSC
Min. Illumination:	Color: 0.05lux @(F1.2, AGC ON), 0 lux with IR
Shutter Time:	1/25 s to 1/10,000 s
Lens:	3.6mm fixed lens
Day&Night:	IR cut filter with auto switch
Image Enhancement:	BLC/3D DNR/D-WDR
Motion Detection	Support
Intelligent Detection(AI)	Humam Detection
Privacy Protection	Support(4 Self-customized Areas)
Wather-Proof:	IP66
Illumination for Infrared Switching:	1~5Lux
Infrared Wavelength:	850nm
Mimumum Illumination:	0 Lux(IR ON)
IR Range:	6 Super IR Leds, up to 15m

### Compression Standard

Video Compression:	H.265/H.264/MJPEG
Video Bit Rate:	512Kbps~6144Kbps(main stream H.265)64kbps~1024kbps(sub stream H.265)64kbps~2048kbps(thr stream H.265)
Audio Compression:	G711U/G711A
Dual Streams:	Yes
Triple Streams:	Yes

### Image

Max. Image Resolution:	4MP HD resolution 2560 x 1440 output
Frame Rate:	30fps(4MP).MAX main stream30fps (D1) .MAX sub stream10fps (FHD).MAX thr stream
Image Settings:	3D NR, D-WDR, Image Flip, Saturation, Brightness, Contrast, Sharpness adjustable via client software, web browser or Smartphone App
Day/Night Switch:	EXT/Day/Night/Auto/Time

### Audio

Line IN/line OUT	Support (1ch)
Build-in MIC/SPK	Optional
Volnume adject	Yes

### Network

Network Protocols:	HTTP, TCP/IP, IPv4/v6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS,DDNS,RTMP,IP Search(Support P2P, NVR, NVS etc.)
System Compatibility:	ONVIF(17.2 with profile S)
On-line Viewing	Max. Support 2Users Simultaneously

### Interface

Communication Interface:	1 RJ45 10M / 100M Ethernet Interface
RCA Audio Interface:	RCA Audio input/output Interface (Optional)
Alarm in/out interface:	Support (1ch) (Optional)
SD card interface	Support TF card (micro TF card, up to 128G) (Optional)
DC Power Plug:	DC Power Femate Interface

### General

Operating Conditions:	-10 °C ~ 60 °C Humidity 95% or less (non-condensing)
Power Supply:	12 V DC ± 10%/PoE(Optional)
Power Consumption:	12 VDC ± 10%, Max Power Consumption Less than 10W (When the infrared lamps turn on)
Weight:	0.35KG

\* Product specifications may change without prior notice.





## IPB-354S

4 MP Fixed Turret Network Camera

### ■ Available Model

IPB-354S IPB-355S (2.8mm/3.6mm)

### ■ Dimension



### ■ Accessory

### ■ Optional



Uin Technology Co., Ltd.

+86-871 63586112

[www.uin-tech.com](http://www.uin-tech.com)

4F,Block 7 Lijincheng High Tech Garden,Longhua District,Shenzhen China

