



WFL-Z33505VUDS2

5 MP Outdoor Auto Tracking 5X/10X Speed Dome Network Camera with Build-in Mic & Speaker



■ Features

- 5.0 megapixel HD IP camera, maximum resolution 2560x1920;
- High-performance main control chip, good picture quality, support humanoid detection alarm and humanoid tracking;
- Support WIFI, support AP mode;
- Support up to 128G TF card storage;
- 2.7-13.5mm 5X; 5-50mm Zoom 10X optical zoom auto focus lens;
- 10pcs array infrared&white light LEDs, irradiation distance 40m, support color night vision;
- Built-in MIC and speakers, support two way audio;
- Pan tilt rotation, horizontal:350°&vertical:90°;
- Waterproof level IP66;
- Support P2P, view & anywhere & anytime;
- Elegant outline and easy installation;
- Provide android & ios APP and professional CMS PC client software;



**■ Specification**

Video	Sensor	5.0 megapixel 1/2.8" SONY335 low lux CMOS
	Video resolution	Main stream: 2560x1920@15fps, 2560x1440@15fps Sub stream: 800x600/800x448@25fps, 640x480/640x352@25fps
	Video compression	H.264/H.265
	Lens	2.7-13.5mm 5X; 5-50mm Zoom 10X optical zoom auto focus lens
	View angle	108.1°- 30.3°
	Night vision	10pcs array infrared&white light LEDs, irradiation distance 40m, support color night vision
Audio	Audio compression	G.726/G.711
	Audio code rate	8Kbps, 16bit
	Audio input/output	Built-in MIC and speakers, support two way audio
Alarm	Motion detection	Can set 4 independent detection areas, can set the sensitivity of 1-100
	Humanoid detection	Support, can be used in conjunction with motion detection to make the alarm more accurate
	Alarm linkage	Alarm recording or capture to Micro SD card, Alarm trigger sound alarm, Alarm capture sent to Email, Alarm recording or capture saved to FTP
	Alarm time	All day or manually customize alarm time period
Interface	Power	5.5*2.1mm power interface
	Ethernet	RJ45 Ethernet interface
	Reset button	Support, press for 5 seconds to reset the camera
	Micro SD card	Support up to 128G micro SD card
	Wireless	IEEE 802.11 b/g/n
	Onvif protocol	Support ONVIF 2.4(backward compatible)
PTZ	Rotation angle	Horizon: 350°, Vertical: 90°
	Horizontal speed	6°-20°/S
	Vertical speed	8°-25°/S
	Preset	Support 8 preset points
General specification	Power consumption	Day: 3W, Night: 15W
	Operating environment	Environment -20°C ~ +60°C (-4°F ~ +140°F), Humidity 10% ~ 90%, non-condensing
	Shell material	Metal shell
	Waterproof level	IP66
	Product size	160mm × 100mm × 175mm (L × W × H)
	Product weight	0.9kg
	Package size	225mm × 205mm × 125mm (L × W × H)
Package weight	1.8kg	

* Product specifications may change without prior notice.





WFL-Z33505VUDS2

5 MP Outdoor Auto Tracking 5X Speed Dome Network Camera with Build-in Mic & Speaker

■ Available Model

WFL-Z33505VUDS2 (2.7-13.5mm Zoom 5X)

WFL-Z33510VUDS2 (5-50mm Zoom 10X)

■ Dimension



■ Accessory

■ Optional



Uin Technology Co., Ltd.

+86-871 63586112

www.uin-tech.com

4F,Block 7 Lijincheng High Tech Garden,Longhua District,Shenzhen China

