



WFL-Z33805VUDS2

8 MP Outdoor Auto Tracking 5X/10X Speed Dome Network Camera with Build-in Mic & Speaker



■ Features

- 8.0 megapixel HD IP camera, maximum resolution 3840x2160;
- High-performance main control chip, good picture quality, support humanoid detection alarm and humanoid tracking;
- Support WIFI, support AP mode;
- Support up to 128G TF card storage;
- 2.7-13.5mm 5X; 5-50mm Zoom 10X optical zoom auto focus lens;
- 10pcs array infrared&white light LEDs, irradiation distance 40m, support color night vision;
- Built-in MIC and speakers, support two way audio;
- Pan tilt rotation, horizontal:350°&vertical:90°;
- Waterproof level IP66;
- Support P2P, view & anywhere & anytime;
- Elegant outline and easy installation;
- Provide android & ios APP and professional CMS PC client software;





WFL-Z33805VUDS2

8 MP Outdoor Auto Tracking 5X Speed Dome Network Camera with Build-in Mic & Speaker

■ Specification

| | | |
|------------------------------|-----------------------|--|
| Video | Sensor | 8.0 megapixel 1/2.8" SONY415 Low Lux CMOS |
| | Video resolution | Main stream: 3840x2160@10fps Sub stream: 1280x720@25fps |
| | Video compression | H.265 |
| | Lens | 2.7-13.5mm 5X; 5-50mm Zoom 10X optical zoom auto focus lens |
| | View angle | 108.1°- 30.3° |
| | Night vision | 10pcs array infrared&white light LEDs, irradiation distance 40m, support color night vision |
| Audio | Audio compression | G.726/G.711 |
| | Audio code rate | 8Kbps, 16bit |
| | Audio input/output | Built-in MIC and speakers, support two way audio |
| Alarm | Motion detection | Can set 4 independent detection areas, can set the sensitivity of 1-100 |
| | Humanoid detection | Support, can be used in conjunction with motion detection to make the alarm more accurate |
| | Alarm linkage | Alarm recording or capture to Micro SD card, Alarm trigger sound alarm, Alarm capture sent to Email, Alarm recording or capture saved to FTP |
| | Alarm time | All day or manually customize alarm time period |
| Interface | Power | 12V/2A 5.5*2.1mm power interface |
| | Ethernet | RJ45 Ethernet interface |
| | Reset button | Support, press for 5 seconds to reset the camera |
| | Micro SD card | Support up to 128G micro SD card |
| | Wireless | IEEE 802.11 b/g/n |
| | Onvif protocol | Support ONVIF 2.4 (backward compatible) |
| PTZ | Rotation angle | Horizon: 350°, Vertical: 90° |
| | Horizontal speed | 6°-20°/S |
| | Vertical speed | 8°-25°/S |
| | Preset | Support 8 preset points |
| General specification | Power consumption | Day: 3W, Night: 15W |
| | Operating environment | Environment -20°C ~ +60°C (-4°F ~ +140°F), Humidity 10% ~ 90%, non-condensing |
| | Shell material | Metal shell |
| | Waterproof level | IP66 |
| | Product size | 160mm × 100mm × 175mm (L × W × H) |
| | Product weight | 0.9kg |
| | Package size | 225mm × 205mm × 125mm (L × W × H) |
| Package weight | 1.8kg | |

* Product specifications may change without prior notice.





WFL-Z33805VUDS2

8 MP Outdoor Auto Tracking 5X Speed Dome Network Camera with Build-in Mic & Speaker

■ Available Model

WFL-Z33805VUDS2 (2.7-13.5mm Zoom 5X)



WFL-Z33810VUDS2 (5-50mm Zoom 10X)

■ Dimension



■ Accessory

■ Optional



Uin Technology Co., Ltd.

+86-871 63586112

www.uin-tech.com

4F,Block 7 Lijincheng High Tech Garden,Longhua District,Shenzhen China

